


TECHNICAL DATA		
FORK AXLE TO CROWN	OE SPEC: 551MM	MAX: 561MM
REAR WHEEL TRAVEL	E2E: 140MM	
TIRE COMPATIBILITY	FRONT: 29X2.6"	REAR: 29X2.6"
HEADSET DIM	TOP: ZS44	BOTTOM: ZS56
SHOCK INFO	E2E: 210M	STROKE: 55MM
SHOCK HARDWARE	UPPER: 25XM8	LOWER: 25XM8
SEATPOST DIAMETER	30.9MM	
SEAT COLLAR DIAMETER	34.9MM	
CHAINLINE	52-55MM	
REAR BRAKE MOUNT	POST MOUNT 180MM	
REAR AXLE	148X12MM	
BEARING SPEC	69012RS: 12X24X6	QTY: 6
	6902-2RS: 15X28X7	QTY: 2

SHIMANO E-SPECIFIC PARTS		
SPEED SENSOR	EWS-S301	
DRIVE UNIT	SHIMANO EP601, EP8	
BATTERY COMPATIBILITY	BT-EN805L, BT-EN806	
BATTERY MOUNT	BM-EN801-A	
CHARGE PORT	EW-CP100	
WIRES	EW-SD300I	
ASSIST MODE SWITCH	SW-E600-L	
DISPLAY	SC-EN600	



## \*CAUTION\*

FOR ALL BOLTS SHOWN ON BIKES RECOMMENDED TO APPLY GREASE AND THREAD LOCKER

THE APPLICATION AREA SHOWN AS LEFT
THREAD LOCKER ON THREAD AREA ONLY
GREASE ON SHAFT AREA ONLY
FOR THOSE BOLTS WITHOUT SHAFT, THREAD LOCKER NEEDED ONLY.

**REAM DEPTH** 

S: 201mm M: 211mm

L: 236mm

XL: 246mm

